

## TYGRIS TECHNICAL DATA SHEET

Industrial Maintenance Aerosols

### Open Gear Lubricant

CODE: **R216**

Provides a tenacious lubricant film to exposed gears and wire ropes

A bituminous reinforced heavy duty lubricant formulated to protect and lubricate exposed gears, wire ropes and other moving parts. Exceptional penetrating and water resistance properties make it ideal for situations where exposure to weather is experienced and its tenacity resists throwing off during use.



Benefits:

- Highly resistant to throw off
- Water resistant for use in adverse weather conditions
- Good penetrating qualities
- Excellent lubricating power
- High pressure foaming discharge imparts excellent penetrative power
- Protects against corrosion, wear and salt
- Resistant to embrittlement over long usage

Technical Data:

Appearance: Dark brown frothy foam drying to a sticky viscous state

Odour: Mineral oil odour

Contents: Blend of petroleum distillates, mineral oil, xylene, bitumen, anti-fling and extreme pressure additives, and hydrocarbon propellants

Solubility: Insoluble in water

Storage: Below 50°C

Flash Point: <0°C

Temperature range: Designed for use at ambient temperatures

Relative Gravity: 0.900

Pack Sizes: 12 x 400ml cans

Directions for Use: Shake can well before use. Spray onto stationary parts from 20 to 30cm. The directional nozzle assists in accurate positioning of the lubricant.