

TYGRIS TECHNICAL DATA SHEET

Industrial Maintenance Aerosols

Clear Acrylic Lacquer

CODE: **R242**

Easy to apply durable protective coating

A fast drying coating used to protect against mild acids, alkalis and general weathering. For sealing and protecting electronics, metal, wood, and paper documents, leaving a smooth, transparent, scratch resistant film with good durability and toughness.

Benefits:

- Fast drying
- Excellent resistance to weathering and sunlight
- High resistance to mild acids and alkalis
- Touch and scratch resistant
- Good resistance to water and salt spray
- Easy to apply

Technical Data:

Appearance: Clear slightly viscous liquid
Odour: Solvent
Contents: Blend of acrylic copolymer, adhesion promoter and ultra violet absorber in acetone, 2-butoxyethanol, 2-methoxy-1-methyl-ethyl acetate in butane/propane propellant
Storage: Below 50°C
Flash Point: <0°C
Temperature range: Up to 50°C continuous
Relative Density: 0.885
Solubility:
Pack Sizes: 12 x 400ml cans
Directions for Use: Clean the surface thoroughly, removing all traces of grease, oil and dirt and un-sound coatings. Shake can well, hold upright and spray evenly onto surface from 25 to 30cm. Allow to dry for 15 to 30 minutes. Allow 20 minutes between applications. After use, invert can and depress actuator. Always test previously coated surfaces for compatibility.

